

MASCHI A MACCHINA - MACHINE TAPS

MASCHI A MACCHINA **HSSE M35 5%Co**

SCANALATURE ELICOIDALI - **ELICA DESTRA 45°** - Imbocco "C"

Filettatura metrica ISO/DIN 13 - UNI 4535 a passo grosso - **6HX**

Rivestimento HPC

MASCHIATURA RIGIDA SINCRONIZZATA

MACHINE TAPS **HSSE M35 5%Co**


SPIRAL FLUTES - **RIGHT HELIX 45°** - Imbocco "C"

ISO Metric Coarse Thread - UNI 4535 - DIN 13 - **6HX**

HPC coated



RIGID TAPPING SYNCRO

HSSE



DIN 371 D ≤ 10mm.

DIN 376 D ≥ 12mm.



DIN 371 / DIN 376							4512.RF5	4514.RF5	4512.RFC5	4514.RFC5
D	p	L ₁	L ₂	d2	∠	⊕			FORATI central hole	FORATI central hole
3	0,5	56	5	3,5	2,7	2,50		-	-	-
4	0,7	63	7	4,5	3,4	3,30		-	-	-
5	0,8	70	8	6,0	4,9	4,20		-	-	-
6	1	80	10	6,0	4,9	5,00		-	-	-
8	1,25	90	13	8,0	6,2	6,75		-	-	-
10	1,5	100	15	10,0	8,0	8,50		-	-	-
12	1,75	110	18	9,0	7,0	10,25	-		-	
14	2	110	20	11,0	9,0	12,00	-		-	
16	2	110	20	12,0	9,0	14,00	-		-	
18	2,5	125	25	14,0	11,0	15,50	-		-	
20	2,5	140	25	16,0	12,0	17,50	-		-	
22	2,5	140	25	18,0	14,5	19,50	-		-	
24	3	160	30	18,0	14,5	21,00	-		-	

Altre dimensioni su richiesta / Other dimensions on demand

Materiali / Application: A1 - A2 - A3 - A4 - A5 / X1 - X2 - X3

N.B.: ≥ M8 centro femmina / ≥ M8 female center