

## MASCHI A MACCHINA - MACHINE TAPS

MASCHI A MACCHINA **HSSE M35 5%Co**

SCANALATURE DIRITTE con IMBOCCO CORRETTO - forma "B"


Filettatura ISO 228/1 - GAS cilindrica BSP

MACHINE TAPS **HSSE M35 5%Co**


STRAIGHT FLUTES SPIRAL POINT (GUN NOSE) - Chamfer form "B"


ISO 228/1 - Whitworth pipe thread BSP

 HSSE



**DIN 5156**



DIN 5156								4543.1	4543.V1	4543.T1	4843.1
D	filetti x 1" TPI	∅ mm	L <sub>1</sub>	L <sub>2</sub>	d <sub>2</sub>	∠		nudi / naked	ST	TIN	ISO 228 + 0,1
1/8	28	9,73	90	15	7,0	5,5	8,80				•
1/4	19	13,16	100	22	11,0	9,0	11,80				•
3/8	19	16,66	100	22	12,0	9,0	15,25				•
1/2	14	20,96	125	25	16,0	12,0	19,00				•
5/8	14	22,91	125	25	18,0	14,5	21,00		-	-	-
3/4	14	26,44	140	25	20,0	16,0	24,50		-	-	-
7/8	14	30,20	150	28	22,0	18,0	28,25		-	-	-
1"	11	33,25	160	30	25,0	20,0	31,00		-	-	-
1 1/8"	11	37,90	170	30	28,0	22,0	35,50		-	-	-
1 1/4"	11	41,91	170	30	32,0	24,0	39,50		-	-	-
* 1 1/2"	11	47,80	190	32	36,0	29,0	45,50		-	-	-
* 1 3/4"	11	53,75	190	32	40,0	32,0	51,50		-	-	-
* 2"	11	59,61	220	40	45,0	35,0	57,00		-	-	-
* Acciaio HSS / HSS Steel											
* Prezzo a richiesta / Price on demand											
Materiali / Application : nudi / naked: A1 - A2 - A3 - A4 / AM1 - AM2 / R1 - R2 ST: A1 - A2 - A3 - A4 / AM1 - AM2 / R1 - R2 / T1 / N1 TIN: A1 - A2 - A3 - A4 / G3 - G4 / AM1 - AM2- AM3 / R1 - R2											