

MASCHI A MACCHINA - MACHINE TAPS

MASCHI A MACCHINA HSS-Co-PM

SCANALATURE ELICOIDALI - **ELICA DESTRA 45°** - Imbocco "C"

Filettatura metrica ISO/DIN 13 - UNI 4535 a passo grosso - **6HX**

Rivestimento **TIN-OX Plus** **Universali**

MASCHIATURA RIGIDA SINCRONIZZATA

MACHINE TAPS HSS-Co PM


SPIRAL FLUTES - **RIGHT HELIX 45°** - Chamfer form "C"

ISO Metric Coarse Thread - UNI 4535 - DIN 13 - **6HX**

TIN-OX Plus coated **Universal use**


RIGID TAPPING SYNCHRO

HSS-Co-PM




4512.U5

4514.U5





4512.UC5

4514.UC5



DIN 371 D ≤ 10mm.

DIN 376 D ≥ 12mm.



DIN 371 / DIN 376							4512.U5	4514.U5	4512.UC5	4514.UC5
D	p	L ₁	L ₂	d ₂	∅				FORATI with central hole	FORATI with central hole
3	0,5	56	5	3,5	2,7	2,50		-	-	-
4	0,7	63	7	4,5	3,4	3,30		-	-	-
5	0,8	70	8	6,0	4,9	4,20		-	-	-
6	1	80	10	6,0	4,9	5,00		-	-	-
8	1,25	90	13	8,0	6,2	6,75		-	-	-
10	1,5	100	15	10,0	8,0	8,50		-	-	-
12	1,75	110	18	9,0	7,0	10,25	-	-	-	-
14	2	110	20	11,0	9,0	12,00	-	-	-	-
16	2	110	20	12,0	9,0	14,00	-	-	-	-
18	2,5	125	25	14,0	11,0	15,50	-	-	-	-
20	2,5	140	25	16,0	12,0	17,50	-	-	-	-
Altre dimensioni su richiesta / Other dimensions on demand										
Materiali / Application: A1 - A2 - A3 - A4 - A5 / X1 - X2 - X3 / G3 - G4 / AM2 - AM3 / R2										

N.B.: ≥ M8 centro femmina / ≥ M8 female center